

Machine Data Sheet

Machine: 1023A	40BSF FLOOR DRILL 3PHASE
<u>Product Dimensions:</u>	
Weight	350kg
Width x Depth x Height	600 x 807 x 2038mm
Base Width x depth	470 x 667mm
<u>Shipping Dimensions</u>	
Length x Width x Height	725 x 755 x 1930mm
Package Type (Pallet or box)	PALLET
<u>Power/Motor</u>	
Motor size	1.5KW
Drive (GH) gearbox (VS) variable speed or (B) Belt	GH
Voltage (240v single) (440v 3 Phase)	440v 3 PHASE
Fitment (Plug connection type)	4 WIRE
Spindle Bearing type	Radial ball Bearing
Spindle speeds (No: and achievable speeds)	6 Speed 75,170, 280, 540, 960, 1600 RPM
<u>Main Specifications</u>	
Type (Bench top or floor)	Floor
Table size (Length x Width x Thickness)	500 x 460 x 45mm
Table Travel Vertical	665mm
Maximum size spindle to Table	775mm
Maximum size spindle to Base	1220mm
Throat (Spindle middle to Column face)	300mm
Column diameter	115mm
Spindle Taper size	4MT M14 thread
Head tilt left to right	45°- 0° - 45°
Table tilt	60°- 0° - 60°
Drill chuck capacity and recommended max drill	13mm & 40mm
Quill diameter	75mm
Quill/Spindle stroke	120mm
<u>Features</u>	
Laser centre?	N
Work light?	Y
Digital speed counter?	N
Depth stop?	Y
Safety interlock guard?	Y

Machine Data Sheet

<u>Other Specifications</u>	
Country of origin	China
Warranty	12 Months
Approximated assembly and setup time	30 mins
CE approved Certificate	CE CERT NO.3
Tee slot size and no of slots (A-B-C-D) no: of slots	A=14 B=25 C=13 D=11mm 4 slots

