

Machine Data Sheet

Machine: 3050	2B12V
<u>Product Dimensions:</u>	
Weight	62kg
Width x Depth x Height	350 x 610 x 980mm
Base Width x depth	270 x 460mm
<u>Shipping Dimensions</u>	
Length x Width x Height	1200 x 800 x 440mm
Package Type (Pallet or box)	Box
<u>Power/Motor</u>	
Motor size	750W
Drive (GH) gearbox (VS) variable speed or (B) Belt	VS
Voltage (240v single) (440v 3 Phase)	240v Single
Fitment (Plug connection type)	3 pin plug, 50hz, 3.4A
Spindle Bearing type	Sealed Roller Bearing
Spindle speeds (No: and achievable speeds)	480-2400 RPM
<u>Main Specifications</u>	
Type (Bench top or floor)	Bench Top
Table size (Length x Width x Thickness)	305 x 310 x 35mm
Table Travel Vertical	365mm
Maximum size spindle to Table	400mm
Maximum size spindle to Base	590mm
Throat (Spindle middle to Column face)	180mm
Column diameter	72mm
Spindle Taper size	2MT
Head tilt left to right	n/a
Table tilt	90-90° (45-45° calibrated)
Drill chuck capacity and recommended max drill	16mm / 20mm max
Quill diameter	47mm
Quill/Spindle stroke	82mm
<u>Features</u>	
Laser centre?	Y
Work light?	Y
Digital speed counter?	Y
Depth stop?	Y
Safety interlock guard?	Y

Machine Data Sheet

<u>Other Specifications</u>	
Country of origin	China
Warranty	12 Months
Approximated assembly and setup time	30 mins
CE approved Certificate	4840319062301
Tee slot size and no of slots (A-B-C-D) no: of slots	A=16 B=26.5 C=10 D=4mm 4 slots

