

Machine Data Sheet

Machine: 3210 and dro	WM210G
<u>Product Dimensions:</u>	
Weight	65kg
Length x Width x Height	900 x 380 x 370mm
Tray Length x Width	805 x 265mm
<u>Shipping Dimensions</u>	
Length x Width x Height (no DRO)	1200 x 800 x 620mm
Length x Width x Height (DRO version)	1200 x 800 x 620mm
<u>Power/Motor</u>	
Motor size	550w
Power Transfer (GH) gearbox or (VS) variable speed	Gear high low (VS)
Spindle speeds (No: and achievable speeds)	50-1250 / 100-2500
Voltage (240v single) (440v 3 Phase)	240v single
Fitment (Plug connection type)	3 pin plug
Current	50hz 6A
<u>Main Specifications</u>	
Maximum swing	210mm
Centre height	105mm
Distance between centre's	400mm
Longitudinal travel (Z)	275mm
Cross slide travel (X)	85mm
Top slide travel (fine Z)	60mm
Spindle taper	Mt3
Tailstock Taper	Mt2
Tailstock quill travel	50mm
Spindle Bore	21mm
Tool shank size recommended for C/L	12mm
Metric and imperial threads	0.3-3MM / 10-44TPI
Chuck mount	Flange Fitting
Spindle Bearings /Drive	Taper roller / Belt drive
<u>Other Specifications</u>	
Country of origin	China
Warranty	12 Months
Approximated assembly and setup time	30 mins
CE approved Certificate	Yes, available upon request

Machine Data Sheet

Additional products	
Optional stand	3210ST
Optional Digital Read Out Kit	4909
X scale	
Z Scale	
Chuck mount sizes	A=72 B=100 C=84PCD D=3MM Also has 4 holes for 4 jaw on flange
Base/tray fixing holes dimensions A-B-C-D	A= N/A B=655 C=125 D=70 mm

