

Machine Data Sheet

Machine: 4009A/B/ADRO/BDRO	GH1322 VARIANTS
<u>Product Dimensions:</u>	
Weight	500kg
Width x Depth x Height	1335 X 750 X 1330mm
Tray Length x Width	N/A
<u>Shipping Dimensions</u>	
Length x Width x Height (no DRO)	1500 x 760 x 1500mm
Length x Width x Height (DRO version)	1500 x 760 x 1500mm
<u>Power/Motor</u>	
Motor size	1.5kw
Power Transfer (GH) gearbox or (VS) variable speed	GH
Spindle speeds (No: and achievable speeds)	8 speeds, 70,115,190,300,460,755,1255,2000
Voltage (240v single) (440v 3 Phase)	240v and 3 Phase available
Fitment (Plug connection type)	3 pin plug or cables
Current	50hz, 3.2A
<u>Main Specifications</u>	
Maximum swing	330mm
Centre height	165mm
Distance between centre's	525mm
Longitudinal travel (Z)	325mm
Cross slide travel (X)	165mm
Top slide travel (fine Z)	70mm
Spindle taper	MT5
Tailstock Taper	MT3
Tailstock quill travel	76mm
Spindle Bore	38mm
Tool shank size recommended for C/L	16mm
Metric and imperial threads	Yes
Chuck mount	D1-4 Camlock
Spindle Bearings /Drive	Taper Roller Bearings
<u>Other Specifications</u>	
Country of origin	China
Warranty	12 Months
Approximated assembly and setup time	45 Mins
CE approved Certificate	Yes, available upon request

Machine Data Sheet

Additional products	
Optional stand	N.A
Optional Digital Read Out Kit	8123
X scale	200mm
Z Scale	350mm
Chuck mount sizes	D1-4 Camlock
Base/tray fixing holes dimensions A-B-C-D	A=350 B=250 C=765 D= 90mm

