

Machine Data Sheet

Machine: 4064	D320
<u>Product Dimensions:</u>	
Weight	310kg
Length x Width x Height	1650 x 760 x 1350mm
Tray Length x Width	1570 x 420mm
<u>Shipping Dimensions</u>	
Length x Width x Height (no DRO)	
Length x Width x Height (DRO version)	1650 x 800 x 1310mm
<u>Power/Motor</u>	
Motor size	1.5kw
Power Transfer (GH) gearbox or (VS) variable speed	VS
Spindle speeds (No: and achievable speeds)	75-435/400-2250rpm
Voltage (240v single) (440v 3 Phase)	240V
Fitment (Plug connection type)	3 Pin Plug
Current	50HZ, 6.5A
<u>Main Specifications</u>	
Maximum swing	320mm
Centre height	160mm
Distance between centre's	880mm
Longitudinal travel (Z)	720mm
Cross slide travel (X)	190mm
Top slide travel (fine Z)	90mm
Spindle taper	MT5
Tailstock Taper	MT3
Tailstock quill travel	85mm
Spindle Bore	38mm
Tool shank size recommended for C/L	12mm
Metric and imperial threads	0.2 – 3.5mm / 8 – 56tpi
Chuck mount	D1-4
Spindle Bearings/Drive	Roller Taper
<u>Other Specifications</u>	
Country of origin	China
Warranty	12 Months
Approximated assembly and setup time	60 mins
CE approved Certificate	Yes, available upon request

Machine Data Sheet

Additional products	
Optional stand	Included, requires assembly
Optional Digital Read Out Kit	Included
X scale	
Z Scale	
Chuck mount sizes	D1-4
Base/tray fixing holes dimensions A-B-C-D	A= 210 B=260 C= 960 D=20 E=210 mm

