

Machine Data Sheet

Machine: 4067	D330 PRO
<u>Product Dimensions:</u>	
Weight	520kg
Length x Width x Height	1850 x 740 x 1660mm
Tray Length x Width	1730 x 495mm
<u>Shipping Dimensions</u>	
Length x Width x Height (no DRO)	
Length x Width x Height (DRO version)	1830x760x1660mm
<u>Power/Motor</u>	
Motor size	1.8kw
Power Transfer (GH) gearbox or (VS) variable speed	GH
Spindle speeds (No: and achievable speeds)	70-2000RPM
Voltage (240v single) (440v 3 Phase)	240V
Fitment (Plug connection type)	3 Pin Plug
Current	7.2A50Hz
<u>Main Specifications</u>	
Maximum swing	330mm
Centre height	165mm
Distance between centre's	1000mm
Longitudinal travel (Z)	760mm
Cross slide travel (X)	190mm
Top slide travel (fine Z)	85mm
Spindle taper	MT5
Tailstock Taper	MT3
Tailstock quill travel	90mm
Spindle Bore	38mm
Tool shank size recommended for C/L	12mm
Metric and imperial threads	Yes 0.25-5mm/6-96tpi
Chuck mount	D1-4
Spindle Bearings/Drive	Roller Taper
<u>Other Specifications</u>	
Country of origin	China
Warranty	12 Months
Approximated assembly and setup time	60 mins
CE approved Certificate	Yes, available upon request

Machine Data Sheet

Additional products	
Optional stand	Included
Optional Digital Read Out Kit	Included
X scale	250mm
Z Scale	800mm
Chuck mount sizes	D1-4
Base/tray fixing holes dimensions A-B-C-D	A= 330 B=170 C=1170 D= 65 mm

