

# Machine Data Sheet

| <b>Machine: 4069A/B/ADRO/BDRO</b>                  | <b>GH1330 VARIANTS</b>                     |
|--|--|
| <b><u>Product Dimensions:</u></b>                  |  |
| Weight   | 600kg                                      |
| Length x Width x Height                            | 1670 X 750 X 1330mm                        |
| Tray Length x Width                                | N/A  |
| <b><u>Shipping Dimensions</u></b>                  |  |
| Length x Width x Height (no DRO)                   | 1700 x 760 x 1500mm                        |
| Length x Width x Height (DRO version)              | 1700 x 760 x 1500mm                        |
| <b><u>Power/Motor</u></b>                          |  |
| Motor size   | 1.5kw                                      |
| Power Transfer (GH) gearbox or (VS) variable speed | GH   |
| Spindle speeds (No: and achievable speeds)         | 8 speeds, 70,115,190,300,460,755,1255,2000 |
| Voltage (240v single) (440v 3 Phase)               | 240v and 3 Phase available                 |
| Fitment (Plug connection type)                     | 3 pin plug or cables                       |
| Current  | 50hz, 3.2A                                 |
| <b><u>Main Specifications</u></b>                  |  |
| Maximum swing over bed / gap                       | 330mm / 450mm                              |
| Centre height                                      | 165mm                                      |
| Distance between centre's                          | 710mm                                      |
| Longitudinal travel (Z)                            | 575mm                                      |
| Cross slide travel (X)                             | 165mm                                      |
| Top slide travel (fine Z)                          | 70mm                                       |
| Spindle taper                                      | MT5  |
| Tailstock Taper                                    | MT3  |
| Tailstock quill travel                             | 76mm                                       |
| Spindle Bore                                       | 38mm                                       |
| Tool shank size recommended for C/L                | 16mm                                       |
| Metric and imperial threads                        | Yes  |
| Chuck mount  | D1-4 Camlock                               |
| Spindle Bearings /Drive                            | Taper Roller Bearings                      |
| <b><u>Other Specifications</u></b>                 |  |
| Country of origin                                  | China                                      |
| Warranty   | 12 Months                                  |
| Approximated assembly and setup time               | 45 Mins                                    |
| CE approved Certificate                            | Yes, available upon request                |

# Machine Data Sheet

| <b>Additional products</b>                |                            |
|---|----------------------------|
| Optional stand                            | N.A                        |
| Optional Digital Read Out Kit             | 8123                       |
| X scale                                   | 200mm                      |
| Z Scale                                   | 600mm                      |
| Chuck mount sizes                         | D1-4 Camlock               |
| Base/tray fixing holes dimensions A-B-C-D | A=350 B=250 C=1055 D= 90mm |

